

OTI CUTTER OKKR-1000 CUTTER FOR BLOCKS, STANDARDIZED AND FLEXIBLE.



Opti Cutter OKKR-1000

Fits all types of pallet production, the operator put the block material into the magazine and the block cutter automatically bring the material in to cutting position, and cut the blocks in to the pre installed length. OKKR-1000 can be programmed to cut several different shapes in length, from the same material. Ex 2 ea. 100mm and then 1 ea. 150mm etc. Options for OKKR-1000: Extension of the machine for material length 4, 5 and 6 meters.

WWW.IMHART.COM



SPECIFICATION MACHINE

Machine specification facts.	Standard performance	
IM Hart machine deliveries. All machines are lics and pneumatics all according to Europea	e delivered according to CE Certification and complete documentation for Electricity, Hydrau- an standard	
Operators	1	
Length	5,0m	
Width	1,0m	
Height	2,0m	
Power	7kw, 20 A, 3x400v+N	
Pneumatic system	7 bar compressed dried air: 450 L/min	
Should be filled and controlled	Container for lubricating oil, Compressor not included	
Hydraulic system	No hydraulic components	
Machine capacity time	36 blocks/min (100x100)	
Standard equipment performance	Magazine for block material	
Requires cyclone fan for removal of ship		
Requires house diameter	1ea. 150mm	
Cyclone fan capacity	750m³/h	

SPECIFICATION MATERIAL

Material	Solid wood	
Block material	Minimum	Maximum
Length	400 mm	6000 mm
Width	70mm	150mm
Thickness	70mm	100mm
Block length	Chose in program	Chose in program